



Product Service

CERTIFICATE

No. Z2 031366 0025 Rev. 00

Holder of Certificate: **Tayplay Limited**
Friarton Road
13A Riverview Business Park
Perth, PH2 8DF
UNITED KINGDOM

Certification Mark:



Product: **Playground equipment**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713340142

Valid until: 2028-03-07

Date, 2024-08-06

(Tobias Hofmann)

CERTIFICATE

No. Z2 031366 0025 Rev. 00

Model(s):

Brig O'Doon, Clachan, Doune, Duart, Dunnottar, Dunvegan, Fingal, Friarton, Glenfinnan, Jungle Rope, Kessock, Kylesku, Shakkin' Briggie, Single Rope, Skye, Slackline 2 m jungle rope, Slackline 2m rope, Slackline 3 m rope, Slackline 4 m rope, Slackline platform, Sligachan, Smoo, Squinty, Swilcan, Triangle Net, Twisted Ladder, Floors, Neidpath, Active 4000 Slide, Active 6000 Slide, Killercrankie, Rope Hammock

Parameters:

Tayplay TRAIL:

Climbing and balancing climbing trail equipment.
Can provided as standard and bespoke combinations.

Materials TRAIL:

Steel tubes 88.9 mm or 127 mm diameter, with powder coated finished.
Ropes and nets are made from diameter 16 mm, 18 mm or 24 mm nylon covered with steel core.
Sliding tube made of stainless steel panels from HDPE.
Step posts from recycled rubber. Walkway from recycled plastic.
Connecting clamps from cast aluminum and powder coated

Material Slacklines:

Steel post from Ø114.3 x 6.3 mm tube, with 6 mm thick steel top plate and 6 x 12 mm thick connecting lugs, all powder coated.
PUR moulded step on top of post, with combined installed height of 450 mm.
2 m, 3 m and 4 m long ropes from 16 mm braided nylon rope
2 m Jungle Rope from 140 mm PP Fendex Rope w/10mm steel-core.

Materials Active 4000/6000 Slide:

Module dimension: 1.00 m.
Steel material: galvanized and powder lacquered.
Post and beam: Laminated timber, steel tubing 110 mm.
Barrier material: Wood, steel, HPL
Floor material: Wood, steel, composite-steel (recycled polyethene) or HPL-Floor-
Roof material: Wood, steel, polypropylene, HPL.
Chain: Hot galvanized chain with covering in solid polyurethane.
Slide: Stainless steel slide-surface.



CERTIFICATE

No. Z2 031366 0025 Rev. 00

Anchoring:
Sunken Concrete Base
Sunken Steel Base/Frame
Concrete Foundation on Site
Anchoring on Concrete (Expansion Bolt)

**Tested
according to:**

DIN EN 1176-1:2017
DIN EN 1176-11:2014
EN 1176-1:2017
EN 1176-11:2014